



Single Gang



MS SERIES

Remote Accessories For Duct Smoke Detectors

The MS Series remote accessories are designed to be used with Duct Smoke Detectors and other monitoring devices to provide audible and visual indication as well as remote test/reset functions. These devices are constructed of attractive, yet durable brushed stainless steel and mount on a standard single electrical backbox. Remote accessories are usually required by the AHJ (Inspector) for installation. If a duct smoke detector is not wired to a fire system or a remote test station, when the unit goes into alarm, the end user would have to climb up to the duct to manually reset the unit.

Applications: For use with ACI Duct Smoke Detection Systems

The MS Series is covered by ACI's Two (2) Year Limited Warranty. The warranty can be found in the front of ACI's Sensors & Transmitters catalog, as well as on ACI's web site, workaci.com.

PRODUCT SPECIFICATIONS

Power Requirements:	Alarm LED: 15 mA @ 24 VDC Trouble LED: 15 mA @ 24 VDC Pilot LED: 15 mA @ 24 VDC Alarm Horn: 20 mA @ 24 VDC
Sound Pressure:	Alarm Horn: 78 db @ 10ft
Wiring	LEDs/Horn: 6" / 24 AWG pigtails Switches: 6" / 22 AWG pigtails
Product Dimensions:	Single Gang Plate: (H) 4.50" (114.3 mm) x (W) 2.75" (69.85 mm) UL Listed for use with ACI Products and Controls duct smoke detectors including all RW-Series, SM-Series, HS-Series and SL-Series duct smoke detectors
Agency Approvals:	UL URRQ, URRQ7.57425 CSFM 7300-1004:107 MEA 73-92-EVOL25

DIMENSIONAL DRAWING

<p>Single Gang</p> <p>4.50" (114.30mm)</p> <p>2.75" (69.85mm)</p>		<p>.22" (5.59mm)</p>
Front View	Right View	Top View

STANDARD ORDERING | HORN STROBE

Model #	Item #	Pilot LED (Green)	Alarm LED (Red)	Fault/Trouble LED (Yellow)	Push Button Test/Reset	Key Operated Test/Reset	Horn	Single Gang	Double Gang
MS-RA	146791		•					•	
MS-RA/P/R	128330	•	•		•			•	
MS-KA/R	111733		•			•		•	

